

Solar shading system

DUCO Ventilation & Sun Control

DucoSun Cubic 100x37 Unifit

Description

Permanent external shading system made of aluminium. The blades are mounted on site in the supporting structure (horizontally or vertically). This variant of the Cubic 100 blade has a width of 37 mm. The blades are placed at a fixed inclination angle of 0° with a 'Unifit' fork. Together with the rectangular form of the blade this gives a particularly sleek effect.

Version

Blade

- Blade type Cubic 100x37
- Shape of blade rectangular
- Blade height 100 mm
- Blade width 37 mm

Bracket

- Type Unifit
- Inclination angle 0°
- Height 100 mm
- Width 40 mm

Blade fixation

- 2 x self-drilling screw DIN 7504-O Ø 4.8 x 16

Bracket fixation

Type	Material
Directly on supporting structure	<ul style="list-style-type: none"> • 2 x hexagon head bolt DIN 933 M8 x 16 • 2 x washer DIN 125-1A M8
On DUCO mullion	<ul style="list-style-type: none"> • 2 x hexagon head bolt DIN 933 M8 x 16 • 2 x washer DIN 125-1A M8 • 2 x nut plate M8

Accessories

- Coverplates available
 - Aluminium AlMg3, lasered, 3 mm thick

Material and surface treatment

Blade

- Aluminium EN AW-6063 T66 (EN 573-3)
 Profile thickness: min. 1.7 mm
- Finish
 - Naturel anodised (15-20 µm) according to Qualanod
 - Polyester powder coated (60-80 µm) according to Qualicoat Seaside type A (specific RAL codes or textured paint on request)

Bracket

- Aluminium EN AW-6063 T66 (EN 573-3)
- Finish
 - Polyester powder coated (60-80 µm) according to Qualicoat Seaside type A (specific RAL codes or textured paint on request)

Technical specifications

Strength calculation

According to EN 1990, EN 1991, EN 1999