

Solar shading system

DUCO Ventilation & Sun Control

DucoSun Cubic 300 Unifit

Description

Permanent external shading system made of aluminium. The blades are mounted on site in the supporting structure (horizontally or vertically). The Cubic 300 blades are placed at a fixed inclination angle of 0° with a 'Unifit' fork. Together with the rectangular form of the blade this gives a particularly sleek effect.

Version

Blade

- Blade type Cubic 300
- Shape of blade rectangular
- Blade height 300 mm
- Blade width 37 mm

Bracket

- Type Unifit
- Inclination angle 0°
- Height 100 mm
- Width 40 mm

Blade fixation

- 2 x hexagon socket countersunk head screw DIN 7991 M5 x 55
- 2 x washer DIN 125-1A M5
- 2 x lock nut DIN 985 M5

Bracket fixation I

Type	Material
Directly on supporting structure	<ul style="list-style-type: none"> • 2 x hexagon head bolt DIN 933 M8 x 16 • 2 x washer DIN 125-1A M8
On DUCO mullion	<ul style="list-style-type: none"> • 2 x hexagon head bolt DIN 933 M8 x 16 • 2 x washer DIN 125-1A M8 • 2 x nut plate M8

Accessories

- Coverplates available
 - Aluminium AlMg3, lasered, 3 mm thick

Material and surface treatment

Blade

- Aluminium EN AW-6063 T66 (EN 573-3)
 Profile thickness: min. 1,9 mm
- Finish
 - Naturel anodised (15-20 µm) according to Qualanod
 - Polyester powder coated (60-80 µm) according to Qualicoat Seaside type A (specific RAL codes or textured paint on request)

Bracket

- Aluminium EN AW-6063 T66 (EN 573-3)
- Finish
 - Polyester powder coated (60-80 µm) according to Qualicoat Seaside type A (specific RAL codes or textured paint on request)

Technical specifications

Strength calculation

According to EN 1990, EN 1991, EN 1999