

TYPE	DucoSun 150CF Underslung - Mullion 42-72					
DESCRIPTION	External permanent solar shading system					
MULLION TYPE	Mullion 42/72					
SHAPE OF BLADE	Blade 150CF					
PITCH	140 mm					
BLADE WIDTH	150 mm					
BLADE HEIGHT	30 mm					
BLADE ANGLE	60°					
MAX. BLADE LENGTH	6000 mm					
SHIFT DISTANCE	Bracket 350/125/125		Max: 50 mm			
	Bracket 500/150/125		Max: 150 mm			
	Bracket 650/150/125		Max: 300 mm			
MATERIAL	Aluminium : EN AW-6063 T66 (EN 573-3) Mullion : min. 2,5mm Blades : min. 1,3mm Thermoplastic parts : Clips Polyamide PA 6,6 -reinforced with glass fibre Steel parts : Brackets Galvanized (50-60µm) Standard untreated, decorative plate optionally available					
SURFACE TREATMENT	- Standard aluminium anodised (15-20µm) according Qualanod - Polyester powder coated (60-80µm) according Qualicoat Seaside type A - Specific RAL codes and/or textured paint on request					
OPTIONS	- Decorative plate 125/125 & 150/125 - Strut					
MAX SPAN WITHOUT FACIA			Bracket 350/125/125		Bracket 500/150/125	
# Blades	Projection		B=0mm		B=150mm	
9	863		2515		2515	
10	1003		2515		2165	
11	1143		2125		1740	
12	1283		1715		1430	
13	1423		1310		1195	
			B=300mm		B=300mm	
			2515		2515	
			2210		2210	
			1800		1800	
			1495		1495	
			1265		1265	

* all the above mentioned spans apply at a wind pressure of 800Pa.

