


TECHNICAL DATA SHEET



TYPE	DucoSun Cubic 200x48 - MULTIFIT
DESCRIPTION	External permanent solar shading system with fixed blades
SHAPE OF BLADE	Rectangular louvre blade
DIMENSIONS	200 mm x 48 mm
MATERIAL	Aluminium : EN AW-6063 T66 (EN 573-3) Profile thickness : min. 1,5 mm
ANGLE OF BLADE	0° / 15° / 30° / 45°
PITCH OF BLADE (S)	To be determined according to project
MAX. SPAN	4450 mm @ 800Pa
COVERPLATES	Aluminium lasered coverplates - thickness 3 mm (AlMgSi0,5)
MULTIFIT	Aluminium extruded bracket - width 50 mm (EN AW6063-T66 (F25))
FIXATION BLADE	Countersunk bolt M5x55 DIN7991 (AISI 304), through blade
FIXATION COVERPLATE	Self-tapping countersunk bolt M6x30 DIN7500-MZ (AISI 304)
FIXATION MULTIFIT	On Duco mullion or directly against the underlying structure. (Ø8,5)
REACTION TO FIRE	A2-s1,d0 (EN13501-1)
SURFACE TREATMENT	- Standard aluminium anodised (15-20µm) according Qualanod - Polyester powder coated (60-80µm) according Qualicoat Seaside type A




3

2

1

D

D




C

C


B

B



A

A

DucoSun **Cubic 200x48** Multifit - 0°

Date : 28/06/2024

Scale: 1/7,5

DUCO
Ventilation & Sun Control

Bedrijvenlaan 2 - 8630 VEURNE
tel. 0032-58/330066 - fax.0032-58/330067
email: info@duco.eu www.duco.eu
This drawing is the property of Duco Projects NV and cannot be copied or shown
to a third party without prior written authorisation from Duco Projects NV.

Tol. : ISO 2768-mK

Draftsman: JHX

Mat. :

Ref nr. :

Format : A3



outline:

weight:

coat. surf:

Drawing nr. :

mm

kg/m

dm²/m

TF_Cubic 200x48_MF

3

2

1