


TECHNICAL DATA SHEET



TYPE	DucoSun Ellips 150 - UNIFIT 45°
DESCRIPTION	External permanent solar shading system with fixed blades
SHAPE OF BLADE	Blade with elliptical cross-section
DIMENSIONS	150 mm x 35 mm
MATERIAL	Aluminium : EN AW-6063 T66 (EN 573-3) Profile thickness : min. 1,5 mm
ANGLE OF BLADE	45°
PITCH OF BLADE (S)	To be determined according to project
MAX. SPAN	3700 mm @ 800Pa
COVERPLATES	Aluminium lasered coverplates - thickness 3 mm (AlMgSi0,5)
UNIFIT	Aluminium extruded bracket - width 40 mm (EN AW6063-T66 (F25))
FIXATION BLADE	Self-drilling countersunk screw 4.8x16 DIN7504-O (AISI 304)
FIXATION COVERPLATE	Self-tapping countersunk bolt M6x30 DIN7500-MZ (AISI 304)
FIXATION UNIFIT	On Duco mullion or directly against the underlying structure. (Ø8,5)
REACTION TO FIRE	A2-s1,d0 (EN13501-1)
SURFACE TREATMENT	- Standard aluminium anodised (15-20µm) according Qualanod - Polyester powder coated (60-80µm) according Qualicoat Seaside type A




3

2

1

D

D




C

C

B

B




A

A

C.C.

C.C.



DucoSun

Ellips 150

Unifit - 45°

Date : 17/06/2024

Scale: 1/7,5

DUCO
Ventilation & Sun ControlBedrijvenlaan 2 - 8630 VEURNE
tel. 0032-58/330066 - fax.0032-58/330067
email: info@duco.eu www.duco.euThis drawing is the property of Duco Projects NV and cannot be copied or shown
to a third party without prior written authorisation from Duco Projects NV.

Tol. : ISO 2768-mK

Mat. :

Format : A3

outline:

weight:

coat. surf:

mm

kg/m

dm²/m

Draftsman: JHX

Ref nr. :

Drawing nr. :

TF_Ellips 150_UF-45

3

2

1