

TECHNICAL DATA SHEET



Type	DucoGrille Solid ISO F 30Z-P1																			
DESCRIPTION	Thermal insulated glazed inn-louvre, built-in situation into aluminium, wood or PVC																			
SHAPE OF BLADE	30Z punched blades (P1) height 21mm x width 2,5mm																			
PITCH	37,5 mm																			
FRAME WIDTH	63 mm																			
GLASS THICKNESS	24/28/32/36/40/44/48 mm																			
FRAME DEPTH	88 mm (thermally broken)																			
MIN. DIMENSIONS	Width 300mm, Height 300mm. Exception on request.																			
MAX. DIMENSIONS	Width 2900 mm if Height < 1250mm. Height 2900 mm if Width < 1250mm.																			
MESH	Aluminium extrusions are perforated and act as insect mesh																			
DRIP TRAY PROFILE	not applicable																			
PLENUM CONNECTION	Round plenum: maximum smallest dimension for length or width - (2*63) Rectangular plenum: height plenum: height louvre - (2*63) width plenum: width louvre - (2*63)																			
U-VALUE	0,9 W/m ² K																			
OPTION	Burglar resistance Class 2 (NEN 5096:2007 and ENV 1627:2011)																			
MATERIAL	Aluminium : EN AW-6063 T66 (EN 573-3) Profile thickness : min. 1,5mm Insulation: Akotherm																			
SURFACE TREATMENT	- standard aluminium anodised (15-20µm) according Qualanod - polyester powder coated (60-80µm) according Qualicoat Seaside type A - specific RAL codes and/or textured paint on request																			
VISUAL FREE AREA	60% per meter of punching																			
PHYSICAL FREE AREA	34%																			
AIR FLOW DATA	<table border="1"> <thead> <tr> <th>(EN13030)</th> <th>standard</th> </tr> </thead> <tbody> <tr> <td>Ce</td> <td>0,243</td> </tr> <tr> <td>K-factor intake</td> <td>16,94</td> </tr> <tr> <td>Cd</td> <td>0,234</td> </tr> <tr> <td>K-factor exhaust</td> <td>18,26</td> </tr> </tbody> </table>		(EN13030)	standard	Ce	0,243	K-factor intake	16,94	Cd	0,234	K-factor exhaust	18,26								
(EN13030)	standard																			
Ce	0,243																			
K-factor intake	16,94																			
Cd	0,234																			
K-factor exhaust	18,26																			
WATER RESISTANCE	<table border="1"> <thead> <tr> <th>(EN13030)</th> <th>standard</th> </tr> </thead> <tbody> <tr> <td>v = 0 m/s</td> <td>B</td> </tr> <tr> <td>v = 0,5 m/s</td> <td>C</td> </tr> <tr> <td>v = 1 m/s</td> <td>C</td> </tr> <tr> <td>v = 1.5 m/s</td> <td>D</td> </tr> <tr> <td>v = 2 m/s</td> <td>D</td> </tr> <tr> <td>v = 2.5 m/s</td> <td>D</td> </tr> <tr> <td>v = 3 m/s</td> <td>D</td> </tr> <tr> <td>v = 3,5 m/s</td> <td>D</td> </tr> </tbody> </table>		(EN13030)	standard	v = 0 m/s	B	v = 0,5 m/s	C	v = 1 m/s	C	v = 1.5 m/s	D	v = 2 m/s	D	v = 2.5 m/s	D	v = 3 m/s	D	v = 3,5 m/s	D
(EN13030)	standard																			
v = 0 m/s	B																			
v = 0,5 m/s	C																			
v = 1 m/s	C																			
v = 1.5 m/s	D																			
v = 2 m/s	D																			
v = 2.5 m/s	D																			
v = 3 m/s	D																			
v = 3,5 m/s	D																			

3

2

1

D

D

C


C

B

B

A

A

DucoGrille Solid **F30Z - ISO - P1**

Datum : 23/03/2023

Schaal : 1:2

DUCO
Ventilation & Sun Control

Bedrijvenlaan 2 - 8630 VEURNE
tel. 0032-58/330066 - fax.0032-58/330067
email: info@duco.eu www.duco.eu
Deze tekening is eigendom van Duco Projects en mag niet gekopieerd
noch getoond worden aan derden zonder schriftelijke toestemming

Tol. : ISO 2768-mK

Getekend : SDN/JHX

Mat. :

Ref nr. :

Formaat : A3



omtrek

gewicht

lakoppervl.

Tekening nr. :

mm

kg/m

dm²/m**DGS-F30Z-ISO-P1**

3

2

1