

TECHNICAL DATA SHEET



Type	DucoGrille Classic N 60HP + options	
DESCRIPTION	Louvre "build-in" wall grille, no flange. Good water resistance.	
SHAPE OF BLADE	60HP	
PITCH	25 mm	
EQUAL LEG OUTER FRAME	0 mm	
INSTALLATION DEPTH	76,5 mm	
FRAME DEPTH	76,5 mm	
MIN. DIMENSIONS	Width 200 mm, Height 200 mm. Exception on request.	
REACTION TO FIRE	A2-s1,d0 (EN13501-1)	
MESH	<ul style="list-style-type: none"> - standard with insectmesh 2.3 x 2.3 mm - optional without mesh - optional with bird mesh 6 x 6 mm - optional with bird mesh 20 x 20 mm 	
DRIP TRAY PROFILE	drip tray integrated in the frame profile, drainage via frame profile	
OPTIONS	test result situation installed in wall	
MATERIAL	Aluminium : EN AW-6063 T66 (EN 573-3) Profile thickness : min. 1,5 mm Blades : min. 1,1 mm	
SURFACE TREATMENT	<ul style="list-style-type: none"> - standard aluminium anodised (15-20 µm) according Qualanod - polyester powder coated (60-80 µm) according Qualicoat Seaside type A - specific RAL codes and/or textured paint on request 	
VISUAL FREE AREA	60%	
PHYSICAL FREE AREA	50%	
IP-CLASS (IEC 60529)	IP4X (electrical installation on min. 100 mm)	
AIR FLOW DATA	(EN13030)	+ options
	Ce	0,197
	K-factor intake	25,77
	Cd	0,253
	K-factor exhaust	15,62
WATER RESISTANCE	(EN13030)	+ options
	v = 0 m/s	A
	v = 0,5 m/s	A
	v = 1 m/s	A
	v = 1.5 m/s	A
	v = 2 m/s	A
	v = 2.5 m/s	A
	v = 3 m/s	B
	v = 3,5 m/s	C

3

2

1

D

D

C


C

B

B

A

A

DucoGrille Classic **N60HP + Options**

Datum : 09/01/2024

Schaal : 1:2

DUCO
Ventilation & Sun Control

Bedrijvenlaan 2 - 8630 VEURNE
tel. 0032-58/330066 - fax.0032-58/330067
email: info@duco.eu www.duco.eu

Deze tekening is eigendom van Duco Projects en mag niet gekopieerd
noch getoond worden aan derden zonder schriftelijke toestemming

Tol. : ISO 2768-mK

Getekend : SVE/JHX

Mat. :

Ref nr. :

Formaat : A3



omtrek

gewicht

lakoppervl.

Tekening nr. :

mm

kg/m

dm²/m

DGC-N60HP + Options

3

2

1