DucoBox Reno

The **NUMBER 1** ventilation box for Social Housing and Flats



Optimal ventilation performance

Copy functionnality for serial housing

Certified Quality



Discover the DucoBox Reno UK

The DucoBox Reno UK is a Central Mechanical Extract Ventilation (CMEV) system, designed for houses and apartment buildings. With its continuous operation, it ensures optimal indoor air quality while delivering exceptional energy efficiency and silent performance.

Whether you are developing social housing projects or modern apartments, the DucoBox Reno UK provides a reliable, **cost-effective solution** for achieving excellent ventilation standards. By integrating cutting-edge technology, this system meets the diverse demands of today's housing market, combining user comfort, sustainability, and straightforward compliance with UK building regulations.



What distinguishes this ventilation box?



OPTIMAL VENTILATION PERFORMANCE

2

COPY FUNCTIONALITY FOR SERIAL HOUSING 3

CERTIFIED QUALITY



OPTIMAL VENTILATION PERFORMANCE

- Airflow capacity of 325 m³/h (90 l/s), suitable for ventilating multiple rooms.
- Centralized built-in humidity detection (standard) and optional CO₂-sensor for an optimal indoor air quality.
- Four spigots allow for ventilation of multiple rooms.
- High-efficiency fan with low specific power consumption thanks to its advanced fan and intelligent controls.
- Whisper-quiet operation for maximum comfort.

2 COPY FUNCTIONALITY FOR SERIAL HOUSING

- Optical LED feedback and copy functionality, ideal for social housing and student flats.
- Easily adjust trickle, boost, and purge rates, meeting Part F of the building regulations.
- Installable in any orientation, ensuring flexibility in space-constrained environments.
- Fault indication via DUCO user control.
- Wireless RF controls and sensors ensure quick and straightforward installation.



Take the leap towards a green and sustainable future!

With a maximum power consumption of 47 W, the DucoBox Reno is very energy-efficient. Add smart demand management to this and save up to 40 % energy!

3 CERTIFIED QUALITY

- SAP/Appendix Q listed and BRE approved for assured quality and compliance.
- DUCO guarantees the highest quality, using only the best materials and components locally sourced.
- The system comes with a warranty up to 3 years, ensuring a long-term reliability.



DUCOBOX RENO IN FIGURES

Physical characteristics


| Item number | 0000-4948 (plug type G / UK) | | | | |
|------------------------|---------------------------------------|--|--|--|--|
| Airflow at 150 Pa | 325 m³/h (90 l/s) | | | | |
| Width x Height x Depth | 381 x 366 x 204 mm | | | | |
| Weight | 3.1 kg | | | | |
| Colours | Green with white lid | | | | |
| Communication | Duco RF Box sensor CO ₂ | | | | |
| Power cable length | 1.5 m | | | | |

Electrical characteristics

| Unom | 230 VAC – 50 Hz |
|----------|-----------------|
| Inom | 0.37 A |
| Pmax | 47 W |
| Cos (φ) | 0.55 |
| IP class | IP40 |

SAP 2012 results

| Exhaust terminal configuration | SFP (W/l/s) |
|----------------------------------|-------------|
| Kitchen + 1 additional wet room | 0.16 |
| Kitchen + 2 additional wet rooms | 0.19 |
| Kitchen + 3 additional wet rooms | 0.20 |
| Kitchen + 4 additional wet rooms | 0.22 |
| Kitchen + 5 additional wet rooms | 0.24 |
| Kitchen + 6 additional wet rooms | 0.27 |



| | | Noise level Lw* | | | | | |
|----------------------|----------------|----------------------------------|--|--|--|--|--|
| Flow rate Qv m³/h | Pressure Pa | Emission from casing dB(A) | | | | | |
| 325 | 150 | 51 | | | | | |
| 275 | 100 | 47,5 | | | | | |
| 200 | 100 | 42,5 | | | | | |
| 150 | 75 | 38 | | | | | |
| 100 | 75 | 35,5 | | | | | |

| Fan Speed | Test mode | Induct Sound Power Levels, dB re. 1pW | | | | | | | | | |
|--------------|--------------|---------------------------------------|------|------|------|------|------|------|------|------|------|
| | | Octave bands, Hz | | | | | | | SPL | | |
| | | 63 | 125 | 250 | 500 | 1k | 2k | 4k | 8k | LwA | @ 3m |
| 100 % | Casing | 57.1 | 48.6 | 50.6 | 49.0 | 47.3 | 41.5 | 63.3 | 27.6 | 51.0 | 33.5 |
| 100 % | Extract | 76.1 | 71.8 | 70.7 | 64.8 | 55.3 | 51.9 | 45.2 | 35.2 | 66.5 | 49.0 |
| 80 % | Casing | 48.4 | 46.3 | 47.2 | 43.2 | 43.7 | 37.6 | 30.1 | 21.4 | 47.0 | 29.5 |
| 00 % | Extract | 68.0 | 69.7 | 67.8 | 55.8 | 50.4 | 46.7 | 37.9 | 26.5 | 62.0 | 44.5 |
| / O 0/ | Casing | 42.2 | 41.0 | 42.4 | 40.0 | 37.8 | 33.1 | 25.2 | 18.0 | 42.0 | 24.5 |
| 60 % | Extract | 63.3 | 64.2 | 63.1 | 52.2 | 45.5 | 40.3 | 29.2 | 19.1 | 57.0 | 39.5 |
| 40 % | Casing | 40.5 | 38.7 | 38.6 | 36.9 | 32.7 | 29.7 | 20.8 | 13.2 | 38.0 | 20.5 |
| 40 70 | Extract | 59.5 | 59.8 | 55.5 | 48.0 | 43.5 | 35.1 | 21.7 | 9.2 | 51.0 | 33.5 |
| 20 % | Casing | 38.3 | 35.7 | 33.9 | 31.8 | 27.2 | 23.5 | 11.5 | 8.4 | 32.5 | 15.0 |
| | Extract | 55.5 | 54.0 | 46.4 | 41.5 | 37.1 | 28.4 | 13.7 | 4.4 | 44.0 | 26.5 |

100% UNBURDENING?

SEND US YOUR PROJECT!

DUCO offers project support from A to Z. Contact one of our advisors (digitally). Tel. +32 58 33 00 33



SCAN the QR code

or surf to

www.duco.eu/yourproject

